

**KK10-6** KK10 - Single Socket Tee (1" IPS)



**10 and 114 Combination**  
360° swivel tee for stair railings.  
This internal swivel connector eliminates  
the need for specially drilled angle fittings.

Designed to give a 90° butt joint between two pipes. Frequently used for the joint between end uprights and the middle rail on safety railing where the site is straight and level. Also for base ties on racking. This fitting cannot be used where the pipe through sleeve 'A' is required to be joined within the fitting. Type 25 should be used when a join in the pipe is necessary.

Part	Weight	A	B	D	E
10-3	0.15 lbs.	3	3	1.14 in.	0.98 in.
10-4	0.29 lbs.	4	4	1.34 in.	1.26 in.
10-5	0.51 lbs.	5	5	1.61 in.	1.46 in.
10-6	0.64 lbs.	6	6	1.81 in.	1.85 in.
10-65	0.55 lbs.	6	5	1.73 in.	1.46 in.
10-67	0.95 lbs.	6	7	2.17 in.	2.17 in.
10-7	0.99 lbs.	7	7	2.36 in.	2.17 in.
10-75	0.7 lbs.	7	5	2.24 in.	1.46 in.
10-76	0.95 lbs.	7	6	2.24 in.	1.81 in.
10-78	1.39 lbs.	7	8	2.87 in.	2.36 in.
10-8	1.36 lbs.	8	8	2.68 in.	2.36 in.
10-87	1.1 lbs.	8	7	2.48 in.	2.17 in.
10-9	2.13 lbs.	9	9	3.31 in.	2.87 in.
10-98	1.43 lbs.	9	8	2.91 in.	2.52 in.