


R-6-62 Invisiware Receiver Stainless Steel 316. Length 3.56" For 1/8" or 3/16" Cable



INVISIWARE RECEIVER DIMENSIONS

Cable Diameter	1/8" Cable	3/16" Cable	1/4" Cable	5/16" Cable	3/8" Cable
Part Number	R-6-62	R-6-63	R-6-64	R-6-65	R-6-66
"T" Thread	1/8"	3/16"	1/4"	5/16"	3/8"
"H" Hex	3/16"	1/4"	5/16"	3/8"	1/2"
"L" Length	3.56"	3.56"	4.00"	4.00"	4.00"

See "FINISHING OPTIONS" Table



FINISHING OPTIONS FOR INVISIWARE® RECEIVERS

Cable Diameter	1/8" Cable	3/16" Cable	1/4" Cable	5/16" Cable	3/8" Cable
Part Number	R-6-62	R-6-63	R-6-64	R-6-65	R-6-66
"T" Thread	1/8"	3/16"	1/4"	5/16"	3/8"
"H" Hex	3/16"	1/4"	5/16"	3/8"	1/2"
"L" Length	3.56"	3.56"	4.00"	4.00"	4.00"
"D" Dia.	3/16"	1/4"	5/16"	3/8"	1/2"
"T" Thread	1/8"	3/16"	1/4"	5/16"	3/8"
"H" Hex	3/16"	1/4"	5/16"	3/8"	1/2"
"L" Length	3.56"	3.56"	4.00"	4.00"	4.00"
"D" Dia.	3/16"	1/4"	5/16"	3/8"	1/2"
"T" Thread	1/8"	3/16"	1/4"	5/16"	3/8"
"H" Hex	3/16"	1/4"	5/16"	3/8"	1/2"
"L" Length	3.56"	3.56"	4.00"	4.00"	4.00"
"D" Dia.	3/16"	1/4"	5/16"	3/8"	1/2"

The Tensioners That Are Hidden Inside The Post - Invisiware® Receiver with Invisiware® Stud

Concealed, swaged, tensioning, through-the-post-mounted fitting suitable for level and pitched runs. Receivers and studs are available for 1/8", 3/16", 1/4", 5/16", and 3/8" diameter 1x19 stainless steel cable.

- The Invisiware® Receiver with Invisiware® Stud can be used with any other fitting on the opposite end of the run.
 - Fitting is placed and concealed within a pre-drilled hole in the metal end post.
 - Receiver is furnished with a Delrin® washer that is installed between the shoulder of the fitting and the end post to protect the surface of the finish of the end post as tension is applied.
 - Stud is swaged onto one end of the cable and threaded into the Receiver installed in the end post. Tension is created by rotating the Receiver (with a hex wrench inserted into its broached end) and drawing the stud into the Receiver.
- For R-6-XX Tools needed: 29/64" drill bit