


**R-8-22** Invisiware Receiver Stainless Steel 316. Length 1.81" For 1/4" Cable



**INVISIWARE RECEIVER DIMENSIONS**

Cable Diameter	1/4" cables	3/16" cables	1/2" cables	5/16" cables	3/8" cables
Part Number	R-8-22	R-8-2X	R-8-3X	R-8-4X	R-8-5X
"T" Thread	1/4"	3/16"	1/2"	5/16"	3/8"
"H" Hex	3/8"	1/2"	1 1/4"	1 1/8"	1 1/4"
"L" Length	1.81"	1.81"	1.81"	1.81"	1.81"

See "FINISHING OPTIONS" table



**FINISHING OPTIONS FOR INVISIWARE RECEIVERS**

Cable Diameter	1/4" cables	3/16" cables	1/2" cables	5/16" cables	3/8" cables
Finish	316	316	316	316	316
1/4" Hex	R-8-22	R-8-22	R-8-22	R-8-22	R-8-22
3/16" Hex	R-8-22	R-8-22	R-8-22	R-8-22	R-8-22
1/2" Hex	R-8-22	R-8-22	R-8-22	R-8-22	R-8-22
5/16" Hex	R-8-22	R-8-22	R-8-22	R-8-22	R-8-22
3/8" Hex	R-8-22	R-8-22	R-8-22	R-8-22	R-8-22
1/4" Length	R-8-22	R-8-22	R-8-22	R-8-22	R-8-22
3/16" Length	R-8-22	R-8-22	R-8-22	R-8-22	R-8-22
1/2" Length	R-8-22	R-8-22	R-8-22	R-8-22	R-8-22
5/16" Length	R-8-22	R-8-22	R-8-22	R-8-22	R-8-22
3/8" Length	R-8-22	R-8-22	R-8-22	R-8-22	R-8-22

## The Tensioners That Are Hidden Inside The Post - Invisiware® Receiver with Invisiware® Stud

Concealed, swaged, tensioning, through-the-post-mounted fitting suitable for level and pitched runs. Receivers and studs are available for 1/8", 3/16", 1/4", 5/16", and 3/8" diameter 1x19 stainless steel cable.

- The Invisiware® Receiver with Invisiware® Stud can be used with any other fitting on the opposite end of the run.
  - Fitting is placed and concealed within a pre-drilled hole in the metal end post.
  - Receiver is furnished with a Delrin® washer that is installed between the shoulder of the fitting and the end post to protect the surface of the finish of the end post as tension is applied.
  - Stud is swaged onto one end of the cable and threaded into the Receiver installed in the end post. Tension is created by rotating the Receiver (with a hex wrench inserted into its broached end) and drawing the stud into the Receiver.
- For R-6-XX Tools needed: 29/64" drill bit