


**R-8-32** Invisiware Receiver Stainless Steel 316. Length 2.03" For 1/4" Cable



**RECEIVER DIMENSIONS**

Cable Diameter	1/4" cables	3/16" cables	1/2" cables	5/16" cables	3/8" cables
Part Number	R-8-32	R-8-3X	R-8-3X	R-10-3X	R-12-3X
"D" Diameter	1.125"	1.125"	1.125"	1.125"	1.125"
"L" Thread	1.1875"	1.1875"	1.1875"	1.1875"	1.1875"
"H" Hex	0.750"	0.750"	1.125"	0.750"	0.750"
"T" Thread	1.125"	1.125"	1.125"	1.125"	1.125"
"S" Length	1.125"	1.125"	1.125"	1.125"	1.125"

See "FINISHING OPTIONS" table



**FINISHING OPTIONS FOR RECEIVER\* WELDED**

Cable Diameter	1/4" cables	3/16" cables	1/2" cables	5/16" cables	3/8" cables
Finish	304	304	304	304	304
1/4" Hex	R-8-32	R-8-32	NA	NA	NA
3/16" Hex	R-8-32	R-8-32	R-8-32	NA	NA
1/2" Hex	R-8-32	R-8-32	R-8-32	R-10-32	R-12-32
5/16" Hex	R-8-32	R-8-32	R-8-32	R-10-32	R-12-32
3/8" Hex	R-8-32	R-8-32	R-8-32	R-10-32	R-12-32
1/4" Dia.	R-8-32	R-8-32	NA	NA	NA
3/16" Dia.	R-8-32	R-8-32	NA	NA	NA
1/2" Dia.	R-8-32	R-8-32	NA	NA	NA
5/16" Dia.	R-8-32	R-8-32	NA	NA	NA
3/8" Dia.	R-8-32	R-8-32	NA	NA	NA

\*See "FINISHING OPTIONS" table

## The Tensioners That Are Hidden Inside The Post - Invisiware® Receiver with Invisiware® Stud

Concealed, swaged, tensioning, through-the-post-mounted fitting suitable for level and pitched runs. Receivers and studs are available for 1/8", 3/16", 1/4", 5/16", and 3/8" diameter 1x19 stainless steel cable.

- The Invisiware® Receiver with Invisiware® Stud can be used with any other fitting on the opposite end of the run.
  - Fitting is placed and concealed within a pre-drilled hole in the metal end post.
  - Receiver is furnished with a Delrin® washer that is installed between the shoulder of the fitting and the end post to protect the surface of the finish of the end post as tension is applied.
  - Stud is swaged onto one end of the cable and threaded into the Receiver installed in the end post. Tension is created by rotating the Receiver (with a hex wrench inserted into its broached end) and drawing the stud into the Receiver.
- For R-6-XX Tools needed: 29/64" drill bit